



CRC (NZ) Food Grade Silicone (Bulk)

CRC Industries (CRC Industries New Zealand)

Chemwatch Hazard Alert Code: 3

Chemwatch: 23-9903

Version No: 8.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Initial Date: 01/11/2009

Revision Date: 29/07/2024

Print Date: 10/06/2026

S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| | |
|-------------------------------|-------------------------------------|
| Product name | CRC (NZ) Food Grade Silicone (Bulk) |
| Chemical Name | Not Applicable |
| Synonyms | Not Available |
| Proper shipping name | HEXANES (contains 2-methylpentane) |
| Chemical formula | Not Applicable |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| | |
|--------------------------|--|
| Relevant identified uses | General purpose silicone-based lubricant. Use according to manufacturer's directions. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. |
|--------------------------|--|

Details of the manufacturer or importer of the safety data sheet

| | |
|-------------------------|---|
| Registered company name | CRC Industries (CRC Industries New Zealand) |
| Address | 10 Highbrook Drive East Tamaki Auckland New Zealand |
| Telephone | +64 9 272 2700 |
| Fax | +64 9 274 9696 |
| Website | www.crc.co.nz |
| Email | - No EMAL ID NEEDED for NZ - JACK |

Emergency telephone number


| | | |
|-------------------------------------|--|-------------------------------------|
| Association / Organisation | CRC Industries (CRC Industries New Zealand) | CHEMWATCH EMERGENCY RESPONSE (24/7) |
| Emergency telephone number(s) | NZ Poisons Centre 0800 POISON (0800 764 766) | +64 800 700 112 (ID#: 23-9903) |
| Other emergency telephone number(s) | 111 (NZ Emergency Services) | +61 3 9573 3188 |

SECTION 2 Hazards identification

Classification of the substance or mixture

| | |
|---|---|
| Classification [1] | Flammable Liquids Category 2, Aspiration Hazard Category 1, Serious Eye Damage/Eye Irritation Category 2, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 2 |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |
| Determined by Chemwatch using GHS/HSNO criteria | 3.1B, 6.1E (aspiration), 6.4A, 6.9B, 9.1B, 6.1E (respiratory tract irritant) |

Label elements

| | |
|---------------------|---|
| Hazard pictogram(s) |  |
| Signal word | Danger |

Hazard statement(s)

| | |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statement(s) Prevention

| | |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe mist/vapours/spray. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P240 | Ground and bond container and receiving equipment. |

Precautionary statement(s) Response

| | |
|----------------|--|
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider. |
| P331 | Do NOT induce vomiting. |
| P370+P378 | In case of fire: Use alcohol resistant foam or normal protein foam to extinguish. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |

Precautionary statement(s) Storage

| | |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |

Precautionary statement(s) Disposal

| | |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|-------------|-----------|--|
| 107-83-5 |]85-95 | <u>2-methylpentane</u> |
| 64742-49-0. | } | <u>Hydrocarbons, C6, isoalkanes, <5% n-hexane</u> |
| 110-54-3 | <5 | <u>n-hexane</u> |
| 63148-62-9 | 2-5 | <u>polydimethylsiloxane</u> |

Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available

SECTION 4 First aid measures

Description of first aid measures

| | |
|-------------|---|
| Eye Contact | If this product comes in contact with the eyes: |
|-------------|---|

| | |
|---------------------|---|
| | <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. |
| Inhalation | <ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay. |
| Ingestion | <ul style="list-style-type: none"> ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice. ▶ Avoid giving milk or oils. ▶ Avoid giving alcohol. |

Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours. For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- ▶ Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- ▶ Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

- ▶ Water spray or fog.
- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ Carbon dioxide.

Do not use a water jet to fight fire.

Special hazards arising from the substrate or mixture

| | |
|-----------------------------|--|
| Fire Incompatibility | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

Advice for firefighters

| | |
|------------------------------|--|
| Fire Fighting | <ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water course. |
| Fire/Explosion Hazard | <ul style="list-style-type: none"> ▶ Liquid and vapour are highly flammable. ▶ Severe fire hazard when exposed to heat, flame and/or oxidisers. ▶ Vapour may travel a considerable distance to source of ignition. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. <p>Combustion products include:</p> <ul style="list-style-type: none"> ▶ carbon dioxide (CO₂) ▶ other pyrolysis products typical of burning organic material. <p>Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. May emit clouds of acrid smoke</p> |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| | |
|---------------------|---|
| Minor Spills | <ul style="list-style-type: none">▶ Remove all ignition sources.▶ Clean up all spills immediately.▶ Avoid breathing vapours and contact with skin and eyes.▶ Control personal contact with the substance, by using protective equipment. |
| Major Spills | <ul style="list-style-type: none">▶ Clear area of personnel and move upwind.▶ Alert Fire Brigade and tell them location and nature of hazard.▶ May be violently or explosively reactive.▶ Wear breathing apparatus plus protective gloves. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

| | |
|--------------------------|---|
| Safe handling | <ul style="list-style-type: none">▶ Containers, even those that have been emptied, may contain explosive vapours.▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers. <p>Contains low boiling substance: Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.</p> <ul style="list-style-type: none">▶ Check for bulging containers.▶ Vent periodically▶ Always release caps or seals slowly to ensure slow dissipation of vapours▶ DO NOT allow clothing wet with material to stay in contact with skin <p>· Electrostatic discharge may be generated during pumping - this may result in fire. · Ensure electrical continuity by bonding and grounding (earthing) all equipment. · Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec). · Avoid splash filling.</p> <ul style="list-style-type: none">▶ Avoid skin contact, including inhalation.▶ Wear protective clothing when risk of exposure occurs.▶ Use in a well-ventilated area.▶ Prevent concentration in hollows and sumps. |
| Other information | <ul style="list-style-type: none">▶ Store in original containers in approved flame-proof area.▶ No smoking, naked lights, heat or ignition sources.▶ DO NOT store in pits, depression, basement or areas where vapours may be trapped.▶ Keep containers securely sealed. |

Conditions for safe storage, including any incompatibilities

| | |
|--------------------------------|--|
| Suitable container | <ul style="list-style-type: none">▶ Packing as supplied by manufacturer.▶ Plastic containers may only be used if approved for flammable liquid.▶ Check that containers are clearly labelled and free from leaks.▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)▶ For manufactured product having a viscosity of at least 250 cSt. |
| Storage incompatibility | <p>Methylpentane:</p> <ul style="list-style-type: none">▶ reacts violently with strong oxidisers▶ is incompatible with nitric acid, sulfuric acid▶ may generate electrostatic charges due to low conductivity▶ Avoid reaction with oxidising agents |

SECTION 8 Exposure controls / personal protection

Control parameters


Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|--|-----------------|-----------------------|----------------------|-----------------------|---------------|---------------|
| New Zealand Workplace Exposure Standards (WES) | 2-methylpentane | Hexane, Other isomers | 500 ppm / 1760 mg/m3 | 3500 mg/m3 / 1000 ppm | Not Available | Not Available |

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|--|------------|-------------------|-------------------|---------------|---------------|--|
| New Zealand Workplace Exposure Standards (WES) | n-hexane | Hexane (n-Hexane) | 20 ppm / 72 mg/m3 | Not Available | Not Available | bio - Exposure can also be estimated by biological monitoring oto - Ototoxin |

Exposure controls

| | |
|--|--|
| Appropriate engineering controls | <p>CARE: Use of a quantity of this material in confined space or poorly ventilated area, where rapid build up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear</p> <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p> |
| Individual protection measures, such as personal protective equipment |  |
| Eye and face protection | <ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent] ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. |
| Skin protection | See Hand protection below |
| Hands/feet protection | <ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care.</p> |
| Body protection | See Other protection below |
| Other protection | <ul style="list-style-type: none"> ▶ Overalls. ▶ PVC Apron. ▶ PVC protective suit may be required if exposure severe. ▶ Eyewash unit. ▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. ▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). ▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. |

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the

computer-generated selection:

CRC (NZ) Food Grade Silicone (Bulk)

| Material | CPI |
|-------------------|-----|
| PE/EVAL/PE | A |
| PVA | A |
| SARANEX-23 2-PLY | A |
| VITON | A |
| VITON/CHLOROBUTYL | A |
| NITRILE | B |
| TEFLON | B |
| BUTYL | C |
| NEOPRENE | C |
| NEOPRENE/NATURAL | C |
| NITRILE+PVC | C |

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|--------------------------|
| up to 10 x ES | AX-AUS P2 | - | AX-PAPR-AUS / Class 1 P2 |
| up to 50 x ES | - | AX-AUS / Class 1 P2 | - |
| up to 100 x ES | - | AX-2 P2 | AX-PAPR-2 P2 ^ |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

| | |
|-----|---|
| PVC | C |
|-----|---|

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| | | | |
|---|--|--|----------------|
| Appearance | Clear water-white liquid with a mild solvent odour; not miscible with water. | | |
| Physical state | Liquid | Relative density (Water = 1) | 0.6694 |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | 254 |
| pH (as supplied) | Not Applicable | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | <-60 | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | 60 (initial) | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | <-18 (TCC) | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | HIGHLY FLAMMABLE. | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | 9.0 | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | 1.7 | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | 21 @20C | Gas group | Not Available |
| Solubility in water | Immiscible | pH as a solution (1%) | Not Applicable |
| Vapour density (Air = 1) | >1 | VOC g/L | 649.3 |
| Heat of Combustion (kJ/g) | Not Available | Ignition Distance (cm) | Not Available |
| Flame Height (cm) | Not Available | Flame Duration (s) | Not Available |
| Enclosed Space Ignition Time Equivalent (s/m3) | Not Available | Enclosed Space Ignition Deflagration Density (g/m3) | Not Available |

SECTION 10 Stability and reactivity

| | |
|---|--|
| Reactivity | See section 7 |
| Chemical stability | <ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| | |
|-------------------------------------|---|
| a) Acute Toxicity | Based on available data, the classification criteria are not met. |
| b) Skin Irritation/Corrosion | Based on available data, the classification criteria are not met. |

| | |
|---|--|
| c) Serious Eye Damage/Irritation | There is sufficient evidence to classify this material as eye damaging or irritating |
| d) Respiratory or Skin sensitisation | Based on available data, the classification criteria are not met. |
| e) Mutagenicity | Based on available data, the classification criteria are not met. |
| f) Carcinogenicity | Based on available data, the classification criteria are not met. |
| g) Reproductivity | Based on available data, the classification criteria are not met. |
| h) STOT - Single Exposure | There is sufficient evidence to classify this material as toxic to specific organs through single exposure |
| i) STOT - Repeated Exposure | There is sufficient evidence to classify this material as toxic to specific organs through repeated exposure |
| j) Aspiration Hazard | There is sufficient evidence to classify this material as an aspiration hazard |

| | |
|---------------------|---|
| Inhaled | <p>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>2-methylpentane has not shown to damage the nervous system (unlike n-hexane).</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p>Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p>Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.</p> |
| Ingestion | <p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p> |
| Skin Contact | <p>This material can cause inflammation of the skin on contact in some persons.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Skin absorption of 2-methylpentane from laboratory studies is slower compared to toluene.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> |
| Eye | There is some evidence to suggest that this material can cause eye irritation and damage in some persons. |
| Chronic | <p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.</p> <p>Harmful: danger of serious damage to health by prolonged exposure through inhalation.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>gamma-diketones are generally toxic to the nervous system. They can occur as commercial products or as metabolic products.</p> |

| | | |
|--|---|--|
| CRC (NZ) Food Grade Silicone (Bulk) | TOXICITY | IRRITATION |
| | Not Available | Not Available |
| 2-methylpentane | TOXICITY | IRRITATION |
| | Oral (Rat) LD50: ~15.84 mg/kg ^[1] | Not Available |
| Hydrocarbons, C6, isoalkanes, <5% n-hexane | TOXICITY | IRRITATION |
| | dermal (rat) LD50: 3.35 mg/kg ^[2] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Inhalation (Rat) LC50: 0.26 mg/L4h ^[2] | Skin: adverse effect observed (irritating) ^[1] |
| | Oral (Rat) LD50: 16.75 mg/kg ^[2] | |
| n-hexane | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: >2000 mg/kg ^[1] | Eye (Rodent - rabbit): 10mg - Mild |
| | Inhalation (Rat) LC50: 48000 ppm4h ^[2] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50: 28710 mg/kg ^[2] | Skin: no adverse effect observed (not irritating) ^[1] |

| | | |
|-----------------------------|--|---|
| polydimethylsiloxane | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: >3000 mg/kg ^[2] | Eye (Rodent - rabbit): 100mg/1H - Mild |
| | Oral (Rat) LD50: >35000 mg/kg ^[2] | Eye (Rodent - rabbit): 100uL/24H - Mild |
| | | Eye (Rodent - rabbit): 100uL/24H - Moderate |
| | | Skin (Rodent - rabbit): 500uL/24H - Mild |

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

| | |
|--|--|
| CRC (NZ) Food Grade Silicone (Bulk) | Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. |
| HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE | <p>Most Low Boiling Point Naphthas (LBPNs) have low acute toxicity to oral, dermal and inhalation routes of exposure, and mild to moderate skin and eye irritating effects. However, some heavier 'cracked' LBPNs (LKBPNs with greater olefinic content) have been found to be more irritating to the skin and eyes compared to non-cracked LBPNs.</p> <p>LBPNs are not known to be sensitising to the skin.</p> <p>Animal studies examined the effects of short-term and longer-term exposure to LBPNs through inhalation or oral routes. In male rats specifically, exposure to LBPNs resulted in kidney-related issues like increased kidney weight, kidney lesions, and hyaline droplet formation. However, the same effects were not seen in female rats, mice, or humans due to a mechanism of action involving a particular enzyme only found in male rats.</p> <p>Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins.</p> <p>The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell. Petroleum contains aromatic (benzene, toluene, ethyl benzene, naphthalene) and aliphatic hydrocarbons (n-hexane), which can result in many detrimental health effects, including, cancer, tumour formation, hearing loss, and nervous system toxicity. Animal testing shows breathing in petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans. Similarly, exposure to gasoline over a lifetime can cause kidney cancer in animals, but the relevance in humans is questionable.</p> <p>Most studies involving gasoline have shown that gasoline does not cause genetic mutation, including all recent studies in living human subjects (such as in petrol service station attendants).</p> <p>Animal studies show concentrations of toluene (>0.1%) can cause developmental effects such as lower birth weight and developmental toxicity to the nervous system of the foetus. Other studies show no adverse effects on the foetus.</p> <p>Prolonged contact with petroleum may result in skin inflammation and make the skin more sensitive to irritation and penetration by other materials.</p> |
| POLYDIMETHYLSILOXANE | <p>No toxic response noted during 90 day subchronic inhalation toxicity studies The no observable effect level is 450 mg/m3. Non-irritating and non-sensitising in human patch test. [Xerox]*</p> <p>Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility.</p> |
| CRC (NZ) Food Grade Silicone (Bulk) & 2-METHYLPENTANE & HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE | No significant acute toxicological data identified in literature search. |
| HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE & N-HEXANE & POLYDIMETHYLSILOXANE | The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. |

| | | | |
|--|---|---------------------------------|---|
| Acute Toxicity | ✗ | Carcinogenicity | ✗ |
| Skin Irritation/Corrosion | ✗ | Reproductivity | ✗ |
| Serious Eye Damage/Irritation | ✓ | STOT - Single Exposure | ✓ |
| Respiratory or Skin sensitisation | ✗ | STOT - Repeated Exposure | ✓ |
| Mutagenicity | ✗ | Aspiration Hazard | ✓ |

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

| CRC (NZ) Food Grade Silicone (Bulk) | Endpoint | Test Duration (hr) | Species | Value | Source |
|--|--|--------------------|-------------------------------|---------------|---------------|
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| 2-methylpentane | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC50(ECx) | 96h | Algae or other aquatic plants | 4.321mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | 4.321mg/l | 2 |
| Hydrocarbons, C6, isoalkanes, <5% n-hexane | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC50 | 48h | Crustacea | 0.64mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | 64mg/l | 2 |
| | NOEC(ECx) | 504h | Crustacea | 0.17mg/l | 2 |
| | LC50 | 96h | Fish | 0.11mg/l | 2 |
| n-hexane | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC50(ECx) | 4h | Algae or other aquatic plants | 0.12mg/L | 4 |
| | LC50 | 96h | Fish | 113mg/L | 4 |
| polydimethylsiloxane | Endpoint | Test Duration (hr) | Species | Value | Source |
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| Legend: | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data | | | | |

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For n-Hexane: Log Kow: 3.17-3.94; Henry's Law Constant: 1.69 atm-m³ mol; Vapor Pressure: 150 mm Hg @ 25 C; Log Koc: 2.90 to 3.61. BOD 5, (if unstated): 2.21; COD: 0.04; ThOD: 3.52.

Atmospheric Fate: n-Hexane is not expected to be directly broken down by sunlight. The main atmospheric removal mechanism is through reactions with hydroxyl radicals, with an approximate half-life of 2.9 days.

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|-----------------|-------------------------|------------------|
| 2-methylpentane | LOW | LOW |
| n-hexane | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|-----------------|-----------------------|
| 2-methylpentane | LOW (LogKOW = 3.2145) |
| n-hexane | MEDIUM (LogKOW = 3.9) |

Mobility in soil

| Ingredient | Mobility |
|-----------------|-----------------------|
| 2-methylpentane | LOW (Log KOC = 124.9) |
| n-hexane | LOW (Log KOC = 149) |

SECTION 13 Disposal considerations

Waste treatment methods

| | |
|-------------------------------------|---|
| Product / Packaging disposal | Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: <ul style="list-style-type: none"> ▶ Reduction |
|-------------------------------------|---|

- ▶ Reuse
- ▶ Recycling
- ▶ Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ▶ **DO NOT allow wash water from cleaning or process equipment to enter drains.**
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible.
- ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- ▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
- ▶ Decontaminate empty containers.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017



Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required

| | |
|------------------|---|
| |  |
| Marine Pollutant |  |
| HAZCHEM | 3YE |

Land transport (UN)

| | | |
|------------------------------------|------------------------------------|----------------|
| 14.1. UN number or ID number | 1208 | |
| 14.2. UN proper shipping name | HEXANES (contains 2-methylpentane) | |
| 14.3. Transport hazard class(es) | Class | 3 |
| | Subsidiary Hazard | Not Applicable |
| 14.4. Packing group | II | |
| 14.5. Environmental hazard | Environmentally hazardous | |
| 14.6. Special precautions for user | Special provisions | Not Applicable |
| | Limited quantity | 1 L |

Air transport (ICAO-IATA / DGR)

| | | |
|----------------------------------|------------------------------------|----------------|
| 14.1. UN number | 1208 | |
| 14.2. UN proper shipping name | Hexanes (contains 2-methylpentane) | |
| 14.3. Transport hazard class(es) | ICAO/IATA Class | 3 |
| | ICAO / IATA Subsidiary Hazard | Not Applicable |
| | ERG Code | 3H |
| 14.4. Packing group | II | |
| 14.5. Environmental hazard | Environmentally hazardous | |

| | | |
|------------------------------------|---|----------------|
| 14.6. Special precautions for user | Special provisions | Not Applicable |
| | Cargo Only Packing Instructions | 364 |
| | Cargo Only Maximum Qty / Pack | 60 L |
| | Passenger and Cargo Packing Instructions | 353 |
| | Passenger and Cargo Maximum Qty / Pack | 5 L |
| | Passenger and Cargo Limited Quantity Packing Instructions | Y341 |
| | Passenger and Cargo Limited Maximum Qty / Pack | 1 L |

Sea transport (IMDG-Code / GGVSee)

| | | |
|------------------------------------|------------------------------------|----------------|
| 14.1. UN number | 1208 | |
| 14.2. UN proper shipping name | HEXANES (contains 2-methylpentane) | |
| 14.3. Transport hazard class(es) | IMDG Class | 3 |
| | IMDG Subsidiary Hazard | P |
| 14.4. Packing group | II | |
| 14.5. Environmental hazard | Marine Pollutant | |
| 14.6. Special precautions for user | EMS Number | F-E, S-D |
| | Special provisions | Not Applicable |
| | Limited Quantities | 1 L |

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|--|----------------|
| 2-methylpentane | Not Applicable |
| Hydrocarbons, C6, isoalkanes, <5% n-hexane | Not Applicable |
| n-hexane | Not Applicable |
| polydimethylsiloxane | Not Applicable |

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|--|----------------|
| 2-methylpentane | Not Applicable |
| Hydrocarbons, C6, isoalkanes, <5% n-hexane | Not Applicable |
| n-hexane | Not Applicable |
| polydimethylsiloxane | Not Applicable |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

| HSR Number | Group Standard |
|------------|--|
| HSR002650 | Solvents (Flammable) Group Standard 2017 |

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

2-methylpentane is found on the following regulatory lists

- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
- New Zealand Inventory of Chemicals (NZIoC)
- New Zealand Workplace Exposure Standards (WES)

Hydrocarbons, C6, isoalkanes, <5% n-hexane is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule; Dangerous Goods 2005 - Schedule 2 Dangerous Goods in Limited Quantities and Consumer Commodities

n-hexane is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

polydimethylsiloxane is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class | Quantity (Closed Containers) | Quantity (Open Containers) |
|--------------|---|----------------------------|
| 3.1B | 100 L in containers more than 5 L | 50 L |
| 3.1B | 250 L in containers up to and including 5 L | 50 L |

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Class of substance | Quantities |
|--------------------|----------------|
| Not Applicable | Not Applicable |

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class | Gas (aggregate water capacity in mL) | Liquid (L) | Solid (kg) | Maximum quantity per package for each classification |
|--------------|--------------------------------------|------------|------------|--|
| 3.1B | | | | 1 L |

Tracking Requirements

Not Applicable

National Inventory Status

| National Inventory | Status |
|---|--|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (2-methylpentane; Hydrocarbons, C6, isoalkanes, <5% n-hexane; n-hexane; polydimethylsiloxane) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | No (polydimethylsiloxane) |
| Japan - ENCS | No (Hydrocarbons, C6, isoalkanes, <5% n-hexane) |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | All chemical substances in this product have been designated as TSCA Inventory 'Active' |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | Yes |
| Vietnam - NCI | Yes |

| National Inventory | Status |
|---|---|
| Russia - FBEPH | Yes |
| UAE - Control List (Banned/Restricted Substances) | No (2-methylpentane; Hydrocarbons, C6, isoalkanes, <5% n-hexane; n-hexane; polydimethylsiloxane) |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| | |
|----------------------|------------|
| Revision Date | 29/07/2024 |
| Initial Date | 01/11/2009 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|----------------|---|
| 7.1 | 10/12/2021 | Classification change due to full database hazard calculation/update. |
| 8.1 | 29/07/2024 | Hazards identification - Classification, Composition / information on ingredients - Ingredients, Accidental release measures - Spills (major) |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code

- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European Inventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory

▸ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

Disclaimer: This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.